

Shakespeare SportRIB Specifications - Summer 2008

Model	520 T	520 P	620 T	620 P	720 P
Tube Diameter	475 – 375 mm	475mm	475 – 375 mm	475mm	500mm
No. Chambers	5	5	5	5	5
Length Overall	5600mm	5600mm	6400mm	6400mm	7250mm
Hull Length	4700mm	4700mm	5650mm	5650mm	6500mm
Waterline Length	3500mm	3500mm	4500mm	4500mm	5300mm
Beam Overall	2200mm	2300mm	2220mm	2320mm	2700mm
Length Internal	4000mm	4000mm	5000mm	5000mm	6200mm
Beam Internal	1420mm	1320mm	1440mm	1340mm	1750mm
Hull & Deck Weight	190 kgs	190 kgs	260 kgs	260 kgs	405 kgs
Displacement <i>ex. eng. (Dry)</i>	385 kgs	395 kgs	475 kgs	495 kgs	875 kgs
RCD Category	C	C	C	C	B/C
Max Payload	650kgs	750kgs	850kgs	1000kgs	1850kgs
Maximum Crew	7	7	9	9	14
Transom Height	600mm	600mm	600mm	600mm	600mm
Engine Configuration	single o/b	single o/b	single o/b	single o/b	single or twin o/b
Engine Leg Length	L (508mm) or XL (635mm)	L (508mm) or XL (635mm)	L (508mm) or XL (635mm)	L (508mm) or XL (635mm)	Single XL (635mm) Twin L (508mm)
Max Engine Weight	195 kgs	200 kgs	250 kgs	275 kgs	400 kgs
Max HP	75 2 stroke or 90 4 stroke	90 2 stroke or 140 4 stroke	150 2 stroke or 175 4 stroke	175 2 stroke or 200 4 stroke	1 x 275 or 2 x 150 2 or 4 stroke
Max Power Kw	85	105	120	150	220
Fuel Tank/Capacity gals.	Above Deck	Above Deck	Above Deck	Above Deck	Underfloor 45 - 75

Shakespeare recommend RIB collars supplied by the following manufacturers:-

Eurocraft GB Ltd.
112 Clydesdale Place
Moss Side
Leyland
Lancs.
Tel: 01772 622856
www.eurocraft.com

Henshaw Inflatables Ltd.
Southgate Road
Wincanton
Somerset
BA9 9RZ
Tel: 01963 33237
www.henshaw.co.uk

Olmec Tubing Ltd.
Collingwood Road
Townstall
Dartmouth
Devon
Tel: 01803 839006
www.olmectubing.co.uk

Tidel Ltd.
Unit 3
Nelson Road Ind Est
Dartmouth
Devon
Tel: 01803 833309
www.tidel.biz

All 520 & 620 model collars are produced in 1200gsm self coloured Hypalon 5 chamber tapered or parallel tubes, fitted with C5 valves and one length of heavy duty D section fendering, lifeline rope patches, 12mm polyester lifelines and four moulded cleat/handles.

All 720 model collars are produced in 1200gsm self coloured Hypalon 5 chamber parallel tubes, fitted with C5 valves and one length of heavy duty D section fendering, lifeline rope patches, 12mm polyester lifelines and six moulded cleat/handles.

Optional pressure relief valves are available to order.

We can also supply a copy of the relevant Certificate of Conformity, and Pressure Test Certificate, which meets and exceeds the requirements of ISO 6185-3.

Please note :- all figures given are nominal at time of publication and subject to change/alteration at anytime at builders discretion - E. & O.E.

Shakespeare International Marine Ltd

Station Yard Station Road Hartlebury Worcestershire DY11 7YJ

Tel: +44+ 01299 250685

Fax: +44+ 01299 250509

www.ribs-by-shakespeare.co.uk

e-mail: sales@nautequipe.co.uk

